



Revision Date: 8/26/2020
Approved by: RR
Version: TL-1

PRODUCT SPECIFICATION

PRODUCT ID # : 10021S-152.5

EPT XTRM PLY CIPP Tape 15 mil -2.5in

Coating

Polymer	TPU
Color	Clear
Sealing	RF, Hot Air, Wedge
Width	3 in

Physical Properties	Units	Test Method	Typical value	
Thickness	mils	ASTM D751	15.0 (± 5%)	
	mm		0.42	
Tearing Resistance (Grave Tear)	lbs.	ASTM D 1004	12	
	N		53	
Dog Bone Tensile	psi	ASTM D 638	6000 (MD)	6000 (TD)
	Mpa		41.1 (MD)	41.1 (MD)
Elongation (Dog Bone Tensile)	%	ASTM D 638	500%	
Dimensional Stability (Max)	%	ASTM D1204	3.0%	
Specific Gravity	g/cc	ASTM D 792	1.2	
Durometer Hardness	Shore A	ASTM D 2240	92	

This document is a draft and is provided for information purpose only.

The information contained herein is subject to change. Final Version will be published as soon as adopted

We believe this information is the best currently available on the subject. It is provided as a suggestion in any appropriate experimentation you may care to undertake. It is subject to revision as additional knowledge, information and experience are gained. We make no guarantee of results and assume no obligation, warranty or liability whatsoever in connection with this information. In case of conflict between standard and metric specifications, standard shall apply