

Product Name: E 610 ND
PVC Coated both sides tarp, Phthalates free.
End Use: Flexitanks, Tanks Liners.

Certified in accord to: EU directive for contact with foodstuff, and SI 5113.

Properties	Typical Characteristics	
Test & Method	English	Metric
Base Fabric	Polyester 1,000 Den 5.3 [Oz/yd²]	Polyester 1,100 Dtx 180 [gr/m²]
Total Weight ASTM D 751	18 [Oz/yd²]	610 [gr/m²]
Width[s]**	59, 81 [inches]	150, 205 [cm]
Breaking Strength - Strip ASTM D 751 method B	285 / 285 [lbs/inch]	2600 / 2600 [N/5 cm]
Tear Strength - Single Rip ASTM D 751 method B, DIN 53356	88 / 77 [lbs]	400 / 350 [N]
Tear Strength - Double Rip B.S 3424 Part 5 method 7B	165 / 165 [lbs]	750 / 750 [N]
Adhesion (HF Welding) ASTM D 751	11 / 11 [lbs/inch]	100 / 100 [N/5 cm]
Cold Bend ASTM D 2136	-22°F	-30°C
Abrasion (Taber) ASTM D 3389 (H-22 1,000 gr)	> 150 cycles to expose the fabric	

**** For special/additional widths, please contact EREZ's representative.**
PROP 65: The product does not require warning label in accord to proposition 65:2018, as the product does not contain a listed substance or/and is under the NSRL "Safe Harbor" levels.
