

Revision Date: 3/7/2025
 Approved by: LJ
 Version: TL-1



PRODUCT SPECIFICATION

PRODUCT ID # : 7102-14454 NR

E2 Sound Safe 144 oz (1.0 lbs/SF) NON REINFORCED

Polymer	PVC
Color	Gray
Sealing	RF, Hot Air, Wedge
Width	54.0 in

Physical Properties	Units	Test Method	Typical value	
Thickness	mils	ASTM D751	110.0 (± 5%)	
	mm		2.79	
Weight	oz/yd ²	ASTM D751	144.0 (± 5%)	
	g/m ²		4882	
Tear Strength	lbs	ASTM D751- B	8 (MD)	8 (TD)
(Tongue Tear)	N		35 (MD)	35 (TD)
Breaking Strength	lbs	ASTM D751-A	200 (MD)	200 (TD)
(Grab Tensile)	N		890 (MD)	890 (TD)
Adhesion- Ply	lb/in	ASTM D751	8	
	N/25mm		35	
Dimensional Stability (Max)	%	ASTM D1204	4.0%	
Flame Resistance		NFPA-701 SS	Pass	
Flame Resistance		UL 94	V-0	
Specific Gravity	g/cc	ASTM D 792	1.8 ± 0.2	

This document is a draft and is provided for information purpose only.
 The information contained herein is subject to change. Final Version will be published as soon as adopted

Product Specifications are minimum values, actual results may be higher

We believe this information is the best currently available on the subject. It is provided as a suggestion in any appropriate experimentation you may care to undertake. It is subject to revision as additional knowledge, information and experience are gained. We make no guarantee of results and assume no obligation, warranty or liability whatsoever in connection with this information. In case of conflict between standard and metric specifications, standard shall apply